

SPECIFICATIONS:

	UniDock-8	UniDock-8T	UniDock-16	Unidock-24
Input	100-240VAC 50/60Hz; 94.2 watts	100-240VAC 50/60Hz; 187.4 watts	100-240VAC 50/60Hz; 187.4 watts	100-240VAC 50/60Hz; 187.4 watts
Output	8 USB-A: 5V/2.1A 2 USB-A: 5V/500mA	16 USB-A: 5V/2.1A 2 USB-A: 5V/500mA	16 USB-A: 5V/2.1A 2 USB-A: 5V/500mA	16 USB-A: 5V/2.1A 2 USB-A: 5V/500mA
Over current/Short circuit/Temperature Protection	Yes	Yes	Yes	yes
AC Leakage Current input	0.25mA max at 240VAC	0.25mA max at 240VAC	0.25mA max at 240VAC	0.25mA max at 240VAC
Ripple And Noise	≤250mV	≤250mV	≤250mV	≤250mV
Turn on delay time	3s max	3s max	3s max	3s max
Rise time	20mS	20mS	20mS	20mS
Efficiency	USB-A: ≥80% USB-C: ≥81.4%	USB-A: ≥80% USB-C: ≥81.4%	USB-A: ≥80% USB-C: ≥81.4%	USB-A: ≥80% USB-C: ≥81.4%
Color	White w/ MedStyle Blue	White w/ MedStyle Blue	White w/ MedStyle Blue	White w/ MedStyle Blue
Size	8 ½"W x 14 ½"D x 6"H	12 ½"W x 13 ½"D x 7"H	14 ½"W x 14 ½"D x 6"H	14 ½"W x 14 ½"D x 6"H
Weight	13.5 lbs	17 lbs.	28 lbs.	28 lbs.
Acrylic top surface treatment	Scratch resistant	Scratch resistant	Scratch resistant	Scratch resistant
White wrap paint treatment	Anti-bacterial powder coat	Anti-bacterial powder coat	Anti-bacterial powder coat	Anti-bacterial powder coat
Accessory	P/N: 46060 wrench, Allen 5/32" T-handle	P/N: 46060 wrench, Allen 5/32" T-handle	P/N: 46060 wrench, Allen 5/32" T-handle	P/N: 46060 wrench, Allen 5/32" T-handle
Operating Temperature Range	0~40°C	0~40°C	0~40°C	0~40°C
Storage Temperature Range	-20 ~ 80°C	-20 ~ 80°C	-20 ~ 80°C	-20 ~ 80°C
Operating Relative Humidity	5% ~ 90% RH	5% ~ 90% RH	5% ~ 90% RH	5% ~ 90% RH
REGULATORY APPROVALS				
Sync-Charge Board	UL	UL	UL	UL
Power Adapter	UL	UL	UL	UL
LIMITED WARRANTY	One year (Proof-of – Purchase Required)	One year (Proof-of – Purchase Required)	One year (Proof-of – Purchase Required)	One year (Proof-of – Purchase Required)