

Specifications:

	DS-UniDock-8-MHB	DS-UniDock-16-MHB	DS-Unidock-24-MHB
Mobile Heartbeat QuickLaunch™	Yes	Yes	Yes
Capacity	8 Devices in most protective cases	16 Devices in most protective cases	24 Devices in most protective cases
SYNC/CHARGE	Yes, Via USB	Yes, Via USB	Yes, Via USB
RFID / Badge Reader	ID Champ Serial IO Bluetooth	ID Champ Serial IO Bluetooth	ID Champ Serial IO Bluetooth
LED Status Indicators	Yes, at each numbered slot	Yes, at each numbered slot	Yes, at each numbered slot
External Attached iOS Charging Holder	Pre-installed to hold iPhone™/iPod™ (2.1 Amp at 5V)	Pre-installed to hold iPhone™/iPod™ (2.1 Amp at 5V)	Pre-installed to hold iPhone™/iPod™ (2.1 Amp at 5V)
External 2 outlet Surge Protector	With 2 USB 2.1Amp 5V	With 2 USB 2.1Amp 5V	With 2 USB 2.1Amp 5V
Input	100-240VAC 50/60Hz; 94.2 watts	100-240VAC 50/60Hz	100-240VAC 50/60Hz
Output	8 USB-A: 5V/2.1A 2 USB-A: 5V/500mA	16 USB-A: 5V/2.1A 2 USB-A: 5V/500mA	16 USB-A: 5V/2.1A 2 USB-A: 5V/500mA
Over current/Short-circuit/Temp. Protection	Yes	Yes	yes
AC Leakage Current input	0.25mA max at 240VAC	0.25mA max at 240VAC	0.25mA max at 240VAC
Ripple and Noise	≤250mV	≤250mV	≤250mV
Turn on delay time	3s max	3s max	3s max
Rise time	20mS	20mS	20mS
Efficiency	USB-A: ≥80% USB-C: ≥81.4%	USB-A: ≥80% USB-C: ≥81.4%	USB-A: ≥80% USB-C: ≥81.4%
Color	White w/ Med Style Blue	White w/ Med Style Blue	White w/ Med Style Blue
Size	8 ½"W x 14 ½"D x 6"H	14 ½"W x 14 ½"D x 6"H	14 ½"W x 14 ½"D x 6"H
Weight	13.5 lbs.	20 lbs.	21 lbs.
Acrylic top surface treatment	Scratch resistance	Scratch resistant	Scratch resistant
White wrap paint treatment	Anti-bacterial powder coat	Anti-bacterial powder coat	Anti-bacterial powder coat
Accessory	P/N: 46060 wrench, Allen 5/32" T-handle	P/N: 46060 wrench, Allen 5/32" T-handle	P/N: 46060 wrench, Allen 5/32" T-handle
Operating Temperature Range	0~40°C	0~40°C	0~40°C
Storage Temperature Range	-20 ~ 80°C	-20 ~ 80°C	-20 ~ 80°C
Operating Relative Humidity	5% ~ 90% RH	5% ~ 90% RH	5% ~ 90% RH
Regulatory Approvals			
Sync-Charge Board	UL	UL	UL
Power Adapter	UL	UL	UL
Limited Warranty	One year (Proof-of –Purchase Required)	One year (Proof-of –Purchase Required)	One year (Proof-of –Purchase Required)